



XANTUS PRODUCTS

SAFETY DATA SHEET

Lockdown PVC Pipe Cement

Part No. LD-04C, LD-04P, LD-11C, LD-11P

SECTION 1 - IDENTIFICATION

Product Identifier

Product Number(s) LD-04C, LD-04P, LD-11C, LD-11P

Product Name Lockdown - 4.5 oz & 11oz cans

Other Means of Identification

Recommended Use and Restrictions on Use

Recommended Use Spray on solvent cleaner/primer & Cement for use on all PVC pipes.

Restrictions on Use None Identified

24 hr Emergency
Phone Number
800-255-3924
(Chem-Tel)

| MANUFACTURER DETAILS | | SUPPLIER DETAILS | |
|----------------------|--|------------------|--|
| Name | Xantus Products | Name | |
| Address | 350 N Walnut st Champaign, IL 61820 | Address | |
| Phone Number | 217-607-5846 | Phone Number | |
| Fax Number | 217-356-0166 | Fax Number | |

SECTION 2 - IDENTIFICATION

Hazard Classification

| HEALTH HAZARDS | | | | PHYSICAL HAZARDS | | | | | |
|-----------------------|--------------------------|----------------------|--------------------------|---|--------------------------|------------------------|--------------------------|---------------------|--------------------------|
| Acute Tox. Oral | <input type="checkbox"/> | Mutagenicity | <input type="checkbox"/> | Unstable Explosive | <input type="checkbox"/> | Refrigerated Liq. Gas | <input type="checkbox"/> | Pyrophoric Solid | <input type="checkbox"/> |
| Acute Tox. Skin | <input type="checkbox"/> | Carcinogenicity | 2 | Explosive | <input type="checkbox"/> | Flammable Liquid | <input type="checkbox"/> | Emits Flammable Gas | <input type="checkbox"/> |
| Acute Tox. Inhalation | <input type="checkbox"/> | Tox. to Reproduction | <input type="checkbox"/> | Flammable Gas | <input type="checkbox"/> | Flammable Solid | <input type="checkbox"/> | Oxidizing Liquid | <input type="checkbox"/> |
| Skin Irritation | <input type="checkbox"/> | STOT SE | 3 | Aerosol | 1 | Self-Reactive Sub. | <input type="checkbox"/> | Oxidizing Solid | <input type="checkbox"/> |
| Eye Irritation | 2 | STOT RE | <input type="checkbox"/> | Oxidizing Gas | <input type="checkbox"/> | Pyrophoric Liquid | <input type="checkbox"/> | Organic Peroxide | <input type="checkbox"/> |
| Resp. Sensitization | <input type="checkbox"/> | Aspiration Hazard | <input type="checkbox"/> | Gas Under Pressure | X | Self-Heating Substance | <input type="checkbox"/> | Corrosive to Metal | <input type="checkbox"/> |
| Skin Sensitization | <input type="checkbox"/> | | <input type="checkbox"/> | ENVIRONMENTAL HAZARDS (GHS Rev 3 Only) | | | | | |
| | <input type="checkbox"/> | | <input type="checkbox"/> | Aquatic Acute | <input type="checkbox"/> | Aquatic Chronic | <input type="checkbox"/> | Ozone Depleting | <input type="checkbox"/> |

Signal Word

Danger

Hazard Pictograms



Hazard Statements

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer.

Precautionary Statements

General

Keep out of reach of children.

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing spray. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.



XANTUS PRODUCTS

SAFETY DATA SHEET

Lockdown PVC Pipe Cement

Part No. LD-04C, LD-04P, LD-11C, LD-11P

| | |
|---|--|
| Response | <i>IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Call a POISON CENTER or doctor if you feel unwell.</i> |
| Storage | <i>Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122°F.</i> |
| Disposal | <i>Dispose of contents/container in accordance with local regulations.</i> |
| Hazards Not Otherwise Classified | <i>None identified.</i> |
| Unknown Acute Toxicity | <i>8.5 % by wt</i> |

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

| ID | INGREDIENT | CAS NUMBER | % WT RANGE* |
|----|---------------------|--------------|-------------|
| 1 | Acetone | 0000067-64-1 | 15 - 40 |
| 2 | Tetrahydrofuran | 0000109-99-9 | 15 - 40 |
| 3 | Methyl Ethyl Ketone | 0000078-93-3 | 10 - 30 |
| 4 | Propane | 0000074-98-6 | 10 - 30 |
| 5 | Polyvinyl Chloride | 0009002-86-2 | 7 - 13 |

* Exact percentages of composition withheld as trade secret

SECTION 4 - FIRST AID MEASURES

Description of First-Aid Measures

| | |
|---------------------------------------|--|
| General | <i>If exposed or concerned seek medical advice/attention.</i> |
| Eye Contact | <i>Immediately flush with clear water for at least 15 minutes, including under the eyelids. Consult a doctor.</i> |
| Skin Contact | <i>Remove with soap and water, rinsing and repeating for 15 minutes. Use skin cream to counter any resulting dryness. Consult a physician if irritation continues. If large skin area is affected, remove contaminated clothing.</i> |
| Ingestion | <i>Do not induce vomiting! Immediately have the victim drink plenty of water. Do not give milk or digestible oils. Keep airways free. Contact a physician. Never give anything by mouth if victim is rapidly losing consciousness, unconscious, or convulsing.</i> |
| Inhalation | <i>Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if symptoms persist or if unconscious.</i> |
| First-Aid Responder Protection | <i>Wear adequate personal protective equipment based on the nature and severity of the emergency.</i> |

Most Important Symptoms and Effects, Both Acute and Delayed

| | |
|---------------------|---|
| Eye Contact | <i>Liquid contact may cause pain along with moderate eye irritation.</i> |
| Skin Contact | <i>Prolonged or repeated exposure may cause skin irritation. Repeated contact may cause drying or flaking of skin. May cause more severe response if confined to skin.</i> |
| Ingestion | <i>Due to being an aerosol, the product does not lend itself to ingestion. Should ingestion occur, it may cause irritation to membranes of the mouth, throat, and gastrointestinal tract resulting in vomiting and/or cramps. Aspiration of vomit into the lungs may cause inflammation, and possible chemical pneumonitis, bronchopneumonia, or pulmonary edema.</i> |
| Inhalation | <i>Prolonged or repeated overexposure is anesthetic. May cause irritation of the respiratory tract, or acute nervous system depression characterized by headache, dizziness, staggering gait, confusion or death. Irritation of the mucous membranes, coughing, and dyspnea are also possible.</i> |

Indication of Immediate Medical Attention and Special Treatment

| | |
|--------------------------------------|----------------------------------|
| Notes to Physician | <i>Treat symptomatically.</i> |
| Specific Treatments/Antidotes | <i>No information available.</i> |
| Immediate Medical Attention | <i>No information available.</i> |

SECTION 5 - FIRE-FIGHTING MEASURES

Extinguishing Media

| | |
|-------------------------------------|---|
| Suitable Extinguishing Media | <i>Water, CO2, dry chemical, or universal aqueous film forming foam</i> |
|-------------------------------------|---|



XANTUS PRODUCTS

SAFETY DATA SHEET

Lockdown PVC Pipe Cement

Part No. LD-04C, LD-04P, LD-11C, LD-11P

Unsuitable Extinguishing Media *Water jet*

Specific Hazards Arising from the Chemical or Mixture

Decomposition Products *Oxides of carbon (CO, CO₂), smoke, and/or vapors*

Hazards from the Product *CONTENTS EXTREMELY FLAMMABLE AND UNDER PRESSURE. In a fire or if heated, a pressure increase will occur which may result in the container bursting. Vapors heavier than air may spread along the ground and travel to an ignition source.*

Advice for Firefighters

Protective Actions *Use water spray to cool fire exposed containers as contents may rupture violently from heat developed pressure.*

Protective Equipment *As with any fire wear SCBA pressure-demand, MSHA/NIOSH approved, and full protective gear.*

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

For Non-Emergency Personnel *No action should be taken by non-emergency personnel without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spill. Remove ignition sources and provide adequate ventilation only if it is safe to do so.*

For Emergency Responders *Use personal protection as recommended in Section 8. Observe precautions provided for non-emergency personnel.*

Environmental Precautions

Precautions *Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.*

Methods and Materials for Containment and Cleaning Up

Containment Procedures *Product is an aerosol, therefore spills and leaks are unlikely. In case of rupture, released content may be contained with oil/solvent absorbent pads, socks, and/or absorbents. DO NOT use combustible material such as sawdust.*

Cleanup Procedures *Spills from aerosol cans are unlikely and are generally of small volume. Large spills are therefore not normally considered a problem. In case of actual rupture, avoid breathing vapors and ventilate area well. Remove sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.*

Other Information *Aerosol products represent a limited hazard and will not spill or leak unless ruptured. In case of rupture contents are generally evacuated from the can rapidly. Area should be ventilated immediately and continuous ventilation provided until all fumes and vapors have been removed. Aerosol cans should never be incinerated or burned. See Section 13 for disposal.*

Prohibited Materials *Combustible absorbent material such as sawdust, use of equipment that may cause sparking.*

SECTION 7 - HANDLING AND STORAGE

Precautions for Safe Handling

General Handling Precautions *KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged or repeated skin contact. Avoid breathing of vapors. Do not incinerate (burn) containers. Always replace overcap when not in use. Avoid use around open flames or other sources of ignition. Exposure to heat or prolonged exposure to sun may cause can to burst. Use only with adequate ventilation, opening doors or windows to achieve cross-ventilation. Wash hands after use.*

Hygiene Recommendations *Do not eat, drink or smoke when using this product. Wash hands thoroughly after use. Remove contaminated clothing and protective equipment before entering eating or smoking areas.*

Conditions for Safe Storage Including Any Incompatibilities

Storage Requirements *Storage of individual cans should be done in an area below 50 °C (122 °F), and away from heat sources. Ensure can is in a secure place to prevent knocking over and accidental rupture. For storage of pallet quantities, compliance with NFPA 30B (Manufacture and Storage of Aerosol Products) is recommended. This product is classified as a Level 3 Aerosol.*

Incompatibilities *Segregate storage away from materials indicated in Section 10*



XANTUS PRODUCTS

SAFETY DATA SHEET

Lockdown PVC Pipe Cement

Part No. LD-04C, LD-04P, LD-11C, LD-11P

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters

Occupational Exposure Limits

| ID | OSHA | | | NIOSH | | | | ACGIH | | | AIHA |
|----|----------|------|---------|----------|----------|---------|---------|----------|---------|---------|------|
| | PEL | STEL | CEILING | IDLH | REL | STEL | CEILING | TLV | STEL | CEILING | WEEL |
| 1 | 1000 ppm | – | – | 2500 ppm | 250 ppm | – | – | 500 ppm | 750 ppm | – | – |
| 2 | 200 ppm | – | – | 2000 ppm | 200 ppm | 250 ppm | – | 50 ppm | 100 ppm | – | – |
| 3 | 200 ppm | – | – | 3000 ppm | 200 ppm | 300 ppm | – | 200 ppm | 300 ppm | – | – |
| 4 | 1000 ppm | – | – | 2100 ppm | 1000 ppm | – | – | 1000 ppm | – | – | – |
| 5 | – | – | – | – | – | – | – | 1 mg/m3 | – | – | – |

Biological Exposure Indices

| ID | DETERMINANT | SAMPLING TIME | BEI | NOTATION |
|----|--------------------------|---------------|---------|----------|
| 1 | Acetone in urine | End of shift | 50 mg/L | Ns |
| 2 | Tetrahydrofuran in urine | End of shift | 8 mg/L | – |
| 3 | MEK in urine | End of shift | 2 mg/L | – |

Other Control Parameters Not Available

Appropriate Engineering Control

Engineering Measures

Use only with adequate ventilation. General ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system may be necessary to control air contamination below that of the lowest OEL from the table above.

Individual Protection Measures

Hygiene Considerations

Avoid breathing vapors and contact with the skin and eyes. Always replace overcap when not in use. Keep out the reach of children. Wash hands after use.

Thermal Protection

This product does not present a thermal hazard.

Respiratory Protection

An approved respirator with organic vapor cartridge may be permissible under certain circumstances where airborne concentrations are expected to exceed occupational exposure limits. If respirators are needed, in the United States compliance with OSHA standard 29 CFR 1910.134 is necessary.

Skin Protection

For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact could occur, use protective clothing impervious to the ingredients listed in Section 2.

Eye/Face Protection

Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling. Where eye contact with this material could occur, chemical splash proof goggles are recommended.

Other Protective Equipment

Safety showers and eye-wash stations should be available in the workplace near where the material will be used.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical Properties

| | | | |
|---------------------|-----------------------------|----------------------------------|------------------------|
| Boiling Point | > 56.1 °C (133.0 °F) | Melting / Freezing Point | > -95.3 °C (-139.6 °F) |
| Flash Point, Liquid | > -17.0 °C (1.4 °F) | Flash Point, Propellant | -104.4 °C (-156.0 °F) |
| Explosive Limits | 1.80% - 13.00% | Autoignition Temperature, Liquid | 404.0 °C (759.2 °F) |
| Flammability | Extremely Flammable Aerosol | Relative Density (H2O = 1) | 0.768 g/cc |
| Molecular Weight | Not Available | Weight | 6.406 lbs/gal |
| Vapor Pressure | 108.00 psig | pH | Not Available |
| Vapor Density | 2.410 g/cc Maximum | Evaporation Rate | Not Available |
| Form | Pressurized Product | Partition Coefficient | Not Available |
| Viscosity | Not Available | Refractive Index | Not Available |
| Odor Threshold | Not Available | Heat of Combustion (ΔHc) | Not Available |
| Odor | Mild odor | Water Solubility | Not Available |



XANTUS PRODUCTS

SAFETY DATA SHEET

Lockdown PVC Pipe Cement

Part No. LD-04C, LD-04P, LD-11C, LD-11P

Appearance / Color

Purple coating

Decomposition Temperature

Not Available

Air Quality Properties

Percent Volatile

92 Wt (96% Vol) Max

VOC Regulatory

5.483 lbs/gal (656.967 g/L)

Percent VOC

58% Wt (63% Vol) Max

VOC Actual

3.715 lbs/gal (445.165 g/L)

Percent HAP

0% Wt (0% Vol) Max

HAP Content

None

Solids/Non Volatile Content

9% Wt (5% Vol) Max

Maximum Incremental Reactivity

1.633 g O3/g

Global Warming Potential

0.728

SECTION 10 - STABILITY AND REACTIVITY

Reactivity

No specific test data related to reactivity is available for this product or its ingredients.

Chemical Stability

This product is stable.

Hazardous Reactions

Under normal conditions of storage and use, hazardous reactions are not expected to occur.

Conditions to Avoid

Keep away from heat, sparks, flame, and red hot metal.

Material Incompatibility

Acids, Activated Carbon, Amines, Ammonia, Bromine, Caustic Alkalies, Halogens, Hexachloromelamine, Hydrogen Peroxide, Isocyanates, Isoprene, Potassium Tert-Butoxide, Pyridines, Strong Acids, Strong Oxidizing Agents, Strong Reducing Agents, Sulfur Dichloride, Trichloromelamine

Decomposition Productions

Oxides of Carbon, Acetic Acid, Aldehydes, Chlorinated Alkenes, Chlorine Gas, Formaldehyde fumes, Hydrogen Chloride fumes, Hydrogen Peroxide, Methanol may be formed depending on fire conditions.

SECTION 11 - TOXICOLOGICAL INFORMATION

Acute Toxicity Estimates (mixture)

Oral LD₅₀

2828 mg/kg

Dermal LD₅₀

4834 mg/kg

Inhalation LC₅₀

67 mg/L 4-hour

Acute Toxicity on Ingredients

| ID | ORAL LD50 | | DERMAL LD50 | | INHALATION LC50 | | |
|----|------------|---------|-------------|---------|-----------------|------|---------|
| | VALUE | SPECIES | VALUE | SPECIES | VALUE | TIME | SPECIES |
| 1 | 5800 mg/kg | rat | 20000 mg/kg | rabbit | 76 mg/m3 | 4h | rat |
| 2 | 1650 mg/kg | rat | >2000 mg/kg | rat | 53.9 mg/L | 4h | rat |
| 3 | 2740 mg/kg | rat | >8050 mg/kg | rat | 11300 ppm | 4h | rat |
| 4 | - | - | - | - | 658 mg/L | 4h | rat |

Health Hazard Classification

Skin Corrosion / Irritation

Classification criteria not met

Eye Damage / Irritation

Category 2

Respiratory Irritation

Classification criteria not met

Respiratory / Skin Sensitization

Classification criteria not met

Germ Cell Mutagenicity

Classification criteria not met

Reproductive Toxicity

Classification criteria not met

STOT - Single Exposure

Category 3

STOT - Repeated Exposure

Classification criteria not met

Aspiration Hazard

Classification criteria not met

Carcinogen Data

| ID | Calif Prop-65 | OSHA | NIOSH | ACGIH | NTP | IARC |
|----|---------------|------|-------|-------|-----|------|
| 2 | - | - | - | A3 | - | - |

Information on the Likely Routes of Exposure

Routes of Exposure

Skin contact, skin absorption, eye contact, inhalation



Information on Physical, Chemical and Toxicological Effects

Symptoms of Exposure Asphyxia, Central Nervous System Depression, Confusion, Dermatitis, Dizziness, Excitation, Skin Irritation, Throat Irritation, Upper Respiratory System Irritation, Vomiting

Delayed and Immediate Effects and also Chronic Effects from Short and Long-Term Exposure

Delayed Effects No known delayed effects.
Immediate Effects No known immediate effects.
Chronic Effects Reports have associated repeated and prolonged occupational overexposure to solvents with irreversible brain and nervous system damage (sometimes referred to as "Solvent or Painter's Syndrome"). Intentional misuse by concentrating and inhaling this product may be harmful or fatal.
Medical Conditions Aggravated May aggravate personnel with pre-existing disorders associated with any of the Target Organs.
Target Organs Central Nervous System, Eyes, Respiratory System, Skin

SECTION 12 - ECOLOGICAL INFORMATION

Acute Aquatic Toxicity

| ID | TYPE | FISH VALUE | PERIOD | TYPE | INVERTEBRATES VALUE | PERIOD | TYPE | AQUATIC PLANTS VALUE | PERIOD | TYPE | MICROORGANISMS VALUE | PERIOD |
|----|------|------------|--------|------|---------------------|--------|------|----------------------|--------|------|----------------------|--------|
| 1 | LC50 | 5549 mg/L | 96h | EC50 | 6100 mg/L | 48h | IC5 | 530 mg/L | 8d | EC5 | 1700 mg/L | 16h |
| 2 | LC50 | 2160 mg/L | 96h | EC50 | >10000 mg/L | 24h | EC10 | >1000 mg/L | 24h | EC10 | >1000 mg/L | 30m |
| 3 | LC50 | 5600 mg/L | 96h | EC50 | 5091 mg/L | 48h | IC5 | >4300 mg/L | 7d | EC5 | 1150 mg/L | 16h |

Ecological Data

| ID | PERSISTENCE AND DEGRADABILITY | | | | BIOACCUMULATIVE POTENTIAL | | MOBILITY |
|----|-------------------------------|----------------|-----------|-----------|---------------------------|--------------|--------------|
| | PERSISTENCE | BOD | COD | ThOD | Pow / Kow | BCF | Koc |
| 1 | 90.9% / 28 days | 1.85 mg/g / 5d | 1.92 mg/L | 2.21 mg/L | -0.24 log Pow | 0.69 BCF | 1.26 log Koc |
| 2 | - | - | 1572 mg/g | - | 0.46 log Pow | - | - |
| 3 | - | 2030 mg/g | 2310 mg/g | 2440 mg/g | 0.29 log Pow | 1.34 log BCF | 0.72 log Koc |
| 4 | - | - | - | - | 2.36 log Pow | 1.47 log BCF | 2.36 log Koc |

Other Adverse Effects No additional information available.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal Characteristics and waste stream classification can change with product use and location. It is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste must be disposed of in compliance with the respective national, federal, state, and/or local regulations.

Waste Disposal of Packaging An aerosol container that does not contain a significant amount of liquid would meet the definition of scrap metal (40 CFR 261.1(c)(6)), and would be exempt from RCRA regulation under 40 CFR 261.6(a)(3)(iv) if it is to be recycled. If containers are to be disposed of (not recycled) it must be managed under all applicable RCRA and state regulations.

Landfill Precautions Not available

Incineration Precautions ** DO NOT INCINERATE ** CONTENTS UNDER PRESSURE **

SECTION 14 - TRANSPORTATION INFORMATION

| Transportation Information | Ground Transportation (DOT) | Air Transportation (IATA) | Ocean Transportation (IMDG) |
|----------------------------|-----------------------------|---------------------------------------|-----------------------------|
| UN Number | UN1950 | UN1950 | UN1950 |
| Proper Shipping Name | Aerosols, Limited Quantity | Aerosols, Flammable, Limited Quantity | Aerosols, Limited Quantity |
| Hazard Class(es) | 2.1 | 2.1 | 2.1 |
| Packaging Group | - | - | - |
| Marine Pollutant | No | No | No |





XANTUS PRODUCTS

SAFETY DATA SHEET

Lockdown PVC Pipe Cement

Part No. LD-04C, LD-04P, LD-11C, LD-11P

Hazard Label(s)



SECTION 15 - REGULATORY INFORMATION

Federal Regulations

| ID | TSCA LISTED | SARA 302 EHS TPQ | RCRA | CERCLA | SARA 313 | FIRE | REACTIVITY | SARA 311/312 ACUTE | CHRONIC | PRESSURE | CLEAN AIR ACT HAP | CLEAN AIR ACT SOCMI | CLEAN WATER ACT |
|----|-------------|------------------|------------|--------|----------|------|------------|--------------------|---------|----------|-------------------|---------------------|-----------------|
| 1 | Yes | - | U002 | 5000 | - | Yes | - | Yes | - | - | - | - | - |
| 2 | Yes | - | U213 | 1000 | - | Yes | - | Yes | - | - | - | - | - |
| 3 | Yes | - | D035, U159 | 5000 | - | Yes | - | Yes | - | - | - | - | - |
| 4 | Yes | - | - | - | - | Yes | - | - | - | - | - | - | - |
| 5 | Yes | - | - | - | - | - | - | - | - | - | - | - | - |

State Regulations

| ID | CA | DE | MA | ME | MN | NJ | NY | PA | WA | WI | WV | | | | | |
|----|------|---------|------------------|------|-------|-----|-----|-------|-----|------|------|-------|--------|----------|-------|-----|
| | P-65 | RQ | RTK CODES | TYPE | RQ | RTK | AIR | WATER | RTK | AIR | LAND | ACUTE | LISTED | PEL TWA | TABLE | TAP |
| 1 | - | 5000 | 2, 4, 5, 6 F8 F9 | - | 20000 | AON | - | - | - | 5000 | 1 | - | Yes-E | 750 ppm | - | - |
| 2 | - | 1000 | 2, 4, 5, 6 F8 | - | 2000 | AO | - | - | - | 1000 | 100 | - | Yes-E | 200 ppm | A | - |
| 3 | - | 5000 | 2, 4, 5, 6 F8 F9 | - | 2000 | ANO | Yes | - | Yes | 5000 | 1 | - | Yes-E | - | - | - |
| 4 | - | F1000** | 2, 4, 5, 6 | - | - | AP | - | - | Yes | - | - | - | Yes | 1000 ppm | - | - |
| 5 | - | - | - | - | - | - | - | - | Yes | - | - | - | - | - | - | - |

SECTION 16 - OTHER INFORMATION

SDS Revision History

Revision 1, 05/14/2014, Original in GHS Version 4 format. (Replaces F7136CT)
 Revision 2, 11/20/2014, Amended to GHS Version 3 format per OSHA (HCS 2012) 29 CFR 1910.1200.

SDS Compliance

This SDS complies with the below listed regulations only. For SDS that comply with other countries, please contact our Regulatory Department at info@xantusproducts.com
 OSHA Hazard Communication Standard (HCS 2012) 29 CFR 1910.1200
 Globally Harmonized System of Classification and Labeling of Chemicals (GHS) Revision 3

Disclaimer of Liability

The information contained herein is based upon data provided to us by our suppliers, and reflects our best judgement. However, no warranty of merchantability, fitness for any use, or any other warranty or guarantee is expressed or implied regarding the accuracy of such data, or the results to be obtained from use thereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of such application. This information is furnished upon the condition that the persons receiving it shall make their own determinations of the suitability of the material for any particular use. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist.